D.R.Distribution Pty.Ltd.

A.B.N.42 055448952 A.C.N.055448952 Phone (02) 96183842 Fax (02) 98292603 Unit 9 No 3 Lancaster St Ingleburn NSW 2565 P.O.Box 568 Ingleburn NSW 1890 www.drdistribution.com.au



Heatstrip®Indoor is a range of medium intensity electric radiant heaters for protected indoor heating applications.

Features:

- Stylish, modern, sleek, slimline design
- Effective & efficient solution for open indoor areas
- Enhanced performance with new profile
- Quiet, maintenance free operation
- Flexible mounting options
- Suitable for commercial and residential applications
- Australian made



Technical Specifications:

| MODEL | POWER (WATTS) | CURRENT (AMPS) | DIMENSIONS (mm) | WEIGHT (Kg) | LEAD LENGTH (mm) | PLUG |
|--------------|------------------|-------------------|--------------------|----------------|------------------------|------|
| DRDTHS 800A | 800 | 3.3 | 624 x 235 x 48 | 4 | 1000 | YES |
| DRDTHS 1200A | 1200 | 5.0 | 924 x 235 x 48 | 6 | 1000 | YES |
| DRDTHS 1800A | 1800 | 7.5 | 1384 x 235 x 48 | 8 | 1000 | YES |
| DRDTHS 2400A | 2400 | 10 | 1834 x 235 x 48 | 11 | 1000 | YES |

HEATER TYPE Medium intensity electric radiant overhead heater with high surface area profiled alloy

OUTPUT Refer to model code chart above

POWER 230240 Volts Nominal at 50—60 Hertz, Single Phase

CONNECTION 3 Core Cable 1.5mm2
APPROVALS AUSTRALIA / NZ

MOUNTING HEIGHT MINIMUM 2.1 m

RECOMMENDED 2.1 m to 2.4 m

(For higher ceiling heights, units can be lowered using optional bracket kits)

MOUNTING OPTIONS Suitable for direct ceiling, angled wall, flush ceiling and TBar ceiling

mounting. Also available for suspension chain mount bracket.

PROTECTION RATING IP45 Protection from water ingress from all directions

COUNTRY OF MANUFACTURE Australia

Mounting Options:

